

# ISUZU X-RIDER



**ISUZU**  
*With you, for the long run*

# MODEL

# D-MAX 250 HO X-RIDER

## DRIVE CONFIGURATION

## 4X4

X-RIDER PACKAGE	
X-Rider Leather-Wrapped Steering Wheel – Red Stitching with Radio Controls and Red Isuzu Badge	Standard
Black Leather Front Bucket Seats with Red Stitching and X-Rider Logo Embroidered on Headrest	Standard
Red Stitching on Gear Lever Cover	Standard
Black Garnish on Vents and Radio	Standard
Black Door Trim Insert with Red 'X'	Standard
18" Diamond-Cut Black Alloy Wheel	Standard
18" Diamond-Cut Black Alloy Spare Wheel	Standard
18" Wheel Cap with Red Isuzu Decal	Standard
X-Rider Decal on Front Door and Tailgate	Standard
Front Bumper Guard	Black
X-Rider Grille – 6-Hole Style	Black
Tubular Side-Steps with X-Rider Decal	Black
X-Rider Sportbar with X-Rider Decal	Black
Projector Headlamps with Integrated LED Daytime Running Lamps (DRL)	Standard
ENGINE	
Engine Code	4JK1-TC HO
Displacement (cc)	2499
No. of Cylinders	4
Compression Ratio	18.1:1
Bore X Stroke (mm)	95.4 X 87.4
No. of Valves	16
Power (kW) @ r/min	100 @ 3400
Torque (Nm) @ r/min	320 @ 1800 – 2800
Turbocharger	Standard
Intercooler	Standard
FUEL	
Fuel Type	Diesel
TRANSMISSION	
Transmission Type	5-Speed Manual
Gear Ratio: 1st	4.008
Gear Ratio: 2nd	2.301
Gear Ratio: 3rd	1.427
Gear Ratio: 4th	1
Gear Ratio: 5th	0.744
Gear Ratio: Reverse	3.651
4WD Selector	Standard
Low Ratio Range	2.482
FRONT DIFFERENTIAL	
Shift on the Fly up to 100 km/h	Standard
Axle Ratio: Final Drive	4.1
REAR DIFFERENTIAL	
Limited Slip Differential	Standard
Axle Ratio: Final Drive	4.1
CHASSIS DESIGN	
Front Wheel Suspension	Coil Over Shock
Rear Wheel Suspension	Leaf-Spring Overslung
Shock Absorbers	Standard
Suspension	High-Ride
Skid Plate Guard	Standard
Engine Sump Guard	Standard
Transfer Case Guard	Standard
Fuel Tank Guard	Standard
WHEELS / TYRES	
Tyre Size	255 / 60 R18
Spare Wheel	18" X 7.5J Alloy
Turning Circle: Curb-to-Curb (m)	12.8
DIMENSIONS	
Length (mm)	5294
Width (mm)	1860
Height (mm)	1790
Wheelbase (mm)	3095
Front / Rear Track (mm)	1570 / 1570
Rear Overhang (mm)	1301
Ground Clearance (mm)	225
Loadbox Length (mm)	1485
Loadbox Width (mm)	1535
Loadbox Depth (mm)	470
Approach Angle (°)	30
Departure Angle (°)	22.7
Breakover Angle (°)	22.4
Wading Depth (mm)	600

MASS / CAPACITIES	
Gross Vehicle Mass (GVM) (kg)	2950
Gross Combined Mass (GCM) (kg)	4950
Tare Mass (kg)	2000
Payload (kg)	891
Fuel Tank Capacity (Litres)	80
LOADBOX FEATURES	
Tiedown Brackets in Loadbox for Load Restraint	4
SAFETY FEATURES	
Anti-Lock Braking System (ABS)	Standard
Electronic Brake-Force Distribution (EBD)	Standard
Brake-Assist System (BAS)	Standard
Side-Impact Protection Bars	Standard
Height-Adjustable 3-Point Seatbelts	Standard
Rear Seatbelt	Standard
Seatbelt Pre-Tensioners	Standard
Driver & Passenger Airbags	Standard
Collapsible Steering Column	Standard
Speed-Sensitive Door Lock	Standard
Warning Triangle Kit	Standard
SECURITY FEATURES	
Remote-Controlled Central Locking	Standard
INTERIOR / EXTERIOR LIGHTING	
Interior Courtesy Lamps	Standard
Illuminated Entry	Standard
Fog Lamps	Front
Headlamps 'ON' Warning Buzzer	Standard
Side Turnlamp on Door	Standard
Rear Taillamps – Combination	Bulb
Centre High-Mounted Stoplamp	Standard
EXTERIOR FEATURES	
Front Bumper – Colour	Body Colour
Rear Bumper – Colour	Black
Exterior Door Handles – Colour	Black
Exterior Mirrors	Black – Manual Adjustment
Mudflaps	Front and Rear
Wipers	Intermittent
INTERIOR FEATURES	
Power-Assisted Steering (PAS)	Hydraulic
Steering Column Adjustment	Tilt
Interior Door Handles – Colour	Black
Gearknob Trim	Urethane
Rear Seat Configuration	60:40-Split Bench Cushion
Seat Adjustment	Manual Height, Reclining
Floor Trim	Carpet with Heel Mat
Driver Footrest	Standard
Air-Conditioner	Manual
Pollen Filter	Standard
Rear Heater Duct	Standard
Inside Rear-View Mirror	Day / Night
Digital Clock	Standard
Auxiliary 12-V Power Socket, Mounted IP	1
Lockable Glove Box	Standard
Utility Box on Glove Box	Standard
Door Trim with Storage Pockets and Integrated Cupholders	Standard
Floor Tunnel / Console with Integrated Cupholder	Standard
Centre Console Storage Box with Lid	Standard
Fuellap Remote	Standard
Window Operation	Power – Front and Rear, Driver Auto Up/Down, Jam Protection
Rear Window	Fixed with Defogger
INFOTAINMENT	
Audio System	AM/FM Radio, Clock, Bluetooth Audio/Hands-Free Phone, CD Player, USB
Audio Input Terminal: Auxiliary, Ipod	Standard
Speakers	4
Antenna	Standard
WARRANTY / SERVICE INTERVALS	
Warranty	3 Years / 100 000 km
Anti-Corrosion Warranty	3 Years / Unlimited km
Service Intervals	5 000 km 10 000 km 15 000 km

Disclaimer: Specifications correct as at time of printing and may subsequently change. Please contact your nearest dealer to confirm any specification changes.